

enLink Status-AF

LoRaWAN Air Velocity Sensor

Synetica's enLink Status-AF, LoRaWAN Air Velocity Sensor measures air velocity with industry leading accuracy ensuring air flow rates for HVAC are monitored at all times.

The system is also suitable for areas where the need to monitor air flow is paramount such as hospital operating rooms and laboratory, industry and pharmaceutical clean rooms.

The enLink Status-AF transmits data using long range LoRa wireless which easily integrates with cloud services or on-site systems via Modbus IP to ensure users are kept up to date with operational performance and to generate alerts when necessary.



Applications



Commercial



Energy



Infrastructure



Pharma



Healthcare



Laboratory

Key Features



Supplied with air velocity probe
100mm to 600mm



Air velocity range 0 – 40m/s



Simple, quick installation



Easy configuration via USB / downlink



LoRa™ wireless, up to 16km range



Battery life 3+ years*



Signal and battery indicator

*Battery life depends on configuration, data rate and environment

enLink Status-AF – LoRaWAN Air Velocity Sensor

Established in 2008, the engineering team at Synetica have many years experience in monitoring and analysing critical environmental information for the facilities management, commercial and industrial sectors.

The enLink Status-AF is suitable for a variety of applications including air velocity monitoring in public buildings and industrial plants. When fitted together with Synetica's enLink Status DP the combination of both systems allow building managers to accurately and continuously measure both air velocity and differential pressure providing invaluable information for HVAC and critical air flow systems.

All our UK manufactured systems incorporate LoRaWAN long range wireless technology so that data can be easily transmitted for analysis. Battery powered versions offer rapid low-cost deployment with the freedom to position monitors for optimal sensing.

If you have a specific requirement for an air, environmental, energy or asset monitoring solution, contact us to learn more about how our precision monitoring technologies could help.

Sensor Characteristics

Range: 0 to 40m/s

Long-term stability $\pm 0.1\%$ FSS

Exceptional zero stability

Selectable bandwidth filter

Up to 7 calibrated ranges, with automatic range selection

Accuracy: 0.1% per range

Integrated 50/60Hz filter

Temperature compensated

UKCA, CE, FCC compliant

Dimensions: 129mm x 67mm x 41mm

**Enclosure IP rating: Standard IP40 / NEMA 1
With optional gasket IP67 / NEMA 4**

About us

Synetica was established in 2008 with the simple idea to revolutionise air quality monitoring, energy usage and remote asset monitoring. Our global customer base relies on our expertise to help them reduce emissions and clean up the air they breathe by allowing them to monitor their energy usage and key environmental parameters via the touch of a button.

www.synetica.net

T: +44 (0)1785 818919 E: enlink@synetica.net

Synetica Limited, Hilton House, 40 High Street, Stone, Staffordshire. ST15 8AU UK

